

Bristol fire pump catalogue pdf

☐

I'm not robot


reCAPTCHA

Next

Bristol fire pump catalogue pdf

Bristol fire pump catalogue pdf.

Our product range includes Bristol NFPA Fire Fighter Suit, Bristol Navy Fireman Coat and Trousers, Bristol Marine Fleet Fire Suit, Bristol Wearing suit, Bristol Fireman Gloves and Bristol Fireman Boot. Interested in this product? RS 1.9 Lakhs / PieceGet Last PreciaMaterial Polish Stereusus / ApplicationIndustrialTrays $\pm$ otodesPatronesPlattersMangas Type Sleevecolormulti ColorBristol NFPA Fire Fighter Costa See full details Are you interested in this product? RS 58,000 / PieceobThe last preciocolorngromaterialnomexpatternPlainbrandbristolGA $\odot$ NeronisExotal LibrepaA $\odot$ Navy Fireman Coat and Trousers See full details Are you interested in this product? RS 90,000 / PieceGet Latest PreEmaterialNomexsusage / ApplicationSecurityMarksMarcabristolTramaA $\pm$ Oreetallawear Typenot ReflectivePatternsleves Typefull SleevesG $\odot$ NeroisExobristol Marine Fleet Fire Suit View Complete Details Are you interested in this product? RS 95,000 / PIECEOBTA $\odot$ n The most recent origin price in indiatmaA $\pm$ omediomaterial100% MangaFull Drill cotton Sleevewear TyperefectiveBristol Use Suit View Complete details Are you interested in this product? RS 14,500 / Pairobhen the most recent priceColorneGromaterialPiel (Buff / Split / Chrome) Finger Type FingEredpatternPlaingA $\odot$ NeroNiseExotypePlassic PolyBolsUsege / ApplicationSecurityGermanyBuivantsBristol Fireman View Complete details. RS 14,000 / PAIROBENTH PRICE REVEALLY MaterialFlame Rubber With Steel Steel Steel / Application Against FlowersCharacteristicsStreetStreetSmaeRecolorTewsTewaNeInDecoribristol Fireman Boot See full details Are you interested in this product? RS 4,600 / PieceObtain the most recent priceMaterial100% Kevlaruso / Application against fireColorLuz BrownPaies of OriginInDiaTramaIn24 inchPatronPackingPackingPackingKbristol Anti-Flash Hood Full details City: Dubai PO Box: 74 582 Country: United Arab Emirates Telephone: +971 4 347 2426 Fax: +971 4 347 2363 Website: website: E-mail: sales@bristol-fire.com Contact person: Basma Sawalha $\pm$ Marketing Manager Type of company: Manufacturer BRISTOL FIRE ENGINEERING , part of Concorde Cordex Group (CCG), founded in 1974 (the first of its kind in the U.S.) and specialized in manufacturing High Quality Fire Combating products, systems and equipment in collaboration with International Know-How and Technology. BRISTOL was one of the first firefighter companies to receive ISO 9001 certification in the Middle East. Do you want to complete or correct the information on this page? Click here! Check the box to request more information.Enter your details in the form below.It should not be used for promotional or job application purposes! Categories: fire, security, fire alarms, detection system, fire pumps, fire extinguishers. Apex Pumps is a successful company based on the skills of its people. We have been manufacturing high specification centrifugal pumps since 1988, with thousands of units operating both in the UK and around the world in facilities where efficiency and reliability are paramount, and we have earned an enviable reputation for the quality and durability of our products. We design and manufacture all our pumps in our Bristol plant and are very proud to be manufactured in Great Britain. Apex Pumps designs and manufactures a wide range of centrifugal pumps for industry, construction services, aquaculture, petrochemical plants and many other similar demanding applications. BRISTOL pumps are designed with the latest design concepts and engineering technology, they are ideal for fire fighting. All manufactured parts are standardized and manufactured with precision for their excellent performance, increasing overall durability and reliable operation. The precision balance of the drives provides stability smooth operation and minimum maintenance. Rotating Parts & Drivers are built with corrosion resistant material. Special metallurgies are also offered on request, on request. The design of the pump allows for on-line service without disturbing the pipes. They are available with electric sets, diesel or electric-Diesel. Getting a quote / Do you need help? Contact Us Marine Firefighting Equipment Delta Fire manufactures and supplies a wide range of marine firefighting equipment. The recent acquisition of the Foundrite range of international couplings and accessories More information A V K I N T E R N A T I O N A L A / S V a l v e s & H y d r a n t s f o r F i r e F i g h t i n g U L / U L C L i s t e d a n d M A p p r o v e d 2 A V K builds long life and good economy in your fire More information BROEN UNIFLEX Accessories for BURNIN ASES BROEN Uniflex TM Accessories for gas burning BROEN Uniflex TM Accessories for gas burning LAB Table of Content Page Table of Content 2 Description Product 3 BROEN Learn more British Standard Underground Hydrant Rango 2 THE NEW AVK BRITISH STANDARD HYDRANT RANGE AVK is the recognised market leader for innovators, manufacturers and suppliers of BS 750 hydrants in the UK. Learn more Worldwide Contacts www.tyco-fire.com Model F through F3 Multisfure Directional Spray Nozzles, Open, High Velocity General Description Multisfure nozzles are open (nonautomatic Read more Morrison Bros. Co. General Product Specifications Tank Mounted Spillbox The spill containment device is manufactured to contain spills and drips that may occur at the filling point in surface storage Learn More FOR AGRICULTURE AND INDUSTRY Industrial Tanks Midwest Fuel Storage Solutions Industrial Tanks Midwest Is Your Source All Of Your Fuel Storage And Fuel Transportation Needs. Our satisfied customers Read more Model F1FR56 Sprinklers Standard Spray Standard Spray Standard Conventional / Vertical Sidewall Model F1FR56 Types of Standard Model F1FR56 Types of Hidden Sprinklers Standard Spray Model More information May 3, 2013 Foam 138a 1. DESCRIPTION Chemguard Chemguard Los monitores oscilantes alimentados estAin diseAados para descargar automAticamente sobre un Airea de diseAzo especAica al activarse el sistema. Son adecuados para su uso MAjs informaciA'n Pgina 1 de 12 TI-S21-07 CH EdiciA'n 1 Cert. No. LRQ 0A 963A 008 ISO 9001 SeleccionA'n de vlvulas de control de temperatura de 2 puertos SeleccionA'n de vlvulas Cmo seleccionar un sistema SeleccionA'n de vlvulas: 1. ALa aplicaciA'n es para calefacciA'n o refrigeraciA'n? MAjs informaciA'n www.kaeser.com Compresores de taller de la serie CLASSIC Desplazamiento: 210 a 40 l/min PresiA'n: 10 bar AQuA© espera de su compresor de taller CLASSIC? MAjs informaciA'n Worldwide Contacts www.tyco-fire.com Series TY-FRB 5.6 K-Factor Horizontal Quick Response. Standard Coverage General Description description in this data sheet are quick response -standard cover, decorative More information A*, A*, A* & A* Model H Series Alarm Check Valve Installation and Maintenance Guide 077 AIRPARK DRIVE STANDISH MICHIGAN TELAN 99-- 00-20 Fax 99--92 www.globesprinkler.com 2 de octubre C-BOLETIN A.C.V.I.M., MAjs informaciA'n GAUGES DE PRESIN Dedicated Sales Rep for Your Area 97%Ratio de llenado EnAeo en 24 Horas Sistema de AlmacAen Soporte TAcnico Programa de Control de Calidad 25 Whaley Avenue Milverton, Ontario N0K MAjs informaciA'n Worldwide Contacts www.tyco-fire.com Series 2.8, 2.6, 8.0 K-Factor Upright, Pendant, Recessed Pendant Sprinklers Quicksee, Cobertura Stard General DescripciA'n The TYCO Series, 2.8, 2.6, 8.0 K-Factor, MAjs informaciA'n 1 de enero de 2011 Aspersor 63a 1. DESCRIPCIN Viking Quick Response Oculado Horizontal Sidewall Sprinkler VK408 es un pequeAzo aspersor de enlace de soldadura y palanca diseAado para instalarse en ocultos MAjs informaciA'n Piezas de repuesto NO SERVICIO LA CALLER SIN UN KIT DE MANTENIMIENTO DISPONIBLE en caso de lesiones corporales graves, muerte o daAaos materiales sustanciales. MAjs informaciA'n P/N: DEF-0613A GasAleo de escape (DEF) Bombas DEF Soluciones DEF Pump has designed a range of unique preconfigured DEF pump packages designed to transfer AdBlue (AUS32) Diesel Exhaust Read more Pressure Relief/Support Valve Prioritization of pressure zones Ensure continued filling of pipes Avoid emptying of pipes Pump overload & cavitation protection Protect the minimum pump flow Excessive More information Pump Standard spray bulletin 036 Model KFR56 Series Response quick spray bulletin standard 036 Model KFR56 Types of sprinklers standard vertical horizontal pendant model KFR56 Types of sprinklers suspension F1/F2/FP More information VOLUEUS AND GAUGES INGERSOLL-RAND AIR LINE VOLVULES AND GAU GES Maintaining a constant air pressure throughout the system is crucial for maximum performance and productivity. Ingersoll-Rand Read more Newsletter 208 Rev. M Sprinkler guards Model C Model D Newsletter 208 Rev. M Model C Sprinkler guards Model C The sprinkler guards of the C series are designed to be mounted on installed sprinklers. They are built Read more Newsletter 013 Rev. M Models F1 Series Standard Response s Newsletter 013 Rev. M Model F156 Types Vertical Standard Pendant Vertical Sidewall Model F156 Recessed Types Pendant/F1/F2/FP More information Provisional amendment NFPA 13 Standard for the installation of irrigation systems 2013 Edition Reference Chapter 6 TIA 13-2 (SC 12.8.24/TIA Log #1054) Note: Text of the issued and incorporated TIA More information Accessories for CO 2 pipe wire The pipe wire references cited in this catalogue meet the requirements specified in the latest edition and modifications of the following ISO Standards: 7-1 (BS21) More information December 19, 2013 Aspersor 122) 1. DESCRIPTION Viking Early Suppression Fast Response (ESFR) VK502 is a quick-response fusible element type sprinkler For use in storage areas More information Monitor Section index Tool of... E2 Daspit Tool e "Camion assembly ... E3 Daspit tool - Model down... E4 Alpha MA-HV4-4 Aluminum bar Monitor ... E5 Alpha-E Tiller Bar Monitor - 3... E6 Sharpshooter More information P Age 1 Section 04 (Doc.NO.A / DBR 001) Short report Firefighter design PD 2 1.0 Scope 2.0 Standards and codes 3.0 Types of proposed system 4.0 Fire hydrant system 5.0 Automatic sprinkler system More information Information -5 seals of sealed lubrication chamber Subbuds of water operation and debris that greatly reduces routine maintenance. The top travel stop nut helps prevent the buckling of stems and damage to the bronze components, making it more information AIR WATER ANTIFREESE FREE DIESEL COMBUSTIBLE OXYGEN-ACETILENE LPG-METHANE EL CATALOGUE CABLE HOLE 2008 TABLE OF CONTENTS SERIES STATIONAL HOLE TOLLES IN PINTED STEEL Page 5- 6 For more information, contact all over the world www.tyco-fire.com Model EC-HS 80 K-Factor, quick response Pida Extended Coverage Horizontal Side Vacuum System Installations by VDS CEA 400, Annex E, LH / OH General description The model More information Features 1. Type of chapaleta of differential chapaleta, lightweight and reliable construction. 2. Pressurized low air system, PSI -TE-2 PSI (0.6 BAR-AT - 1.9 bar) MAX 3. Reset externally. The removal of the cover is no more information Contacts worldwide www.tyco-fire.com Series TY-FRB 5.6 and 8.0 K-Factor Extended Coverage Horizontal Sidewall S Quick and standard response (light hazard) General Description TYCO Series TY-FRB 5.6 and m VDS information Guidelines for water extinguishing systems VDS 2100-09EN Requirements and Test Methods VDS 2100-09EN: 2011-05 (01) Publication: VDS SchadenVerhtungen GmbH AmsterDamer STR. 172-174 50 735 Ktlin, more information Seated valves (PN 16) VF 2 2-way valve, flange VF 3 3-way valve, flange Description VF 2 VF 3 VF 2 and VF 3 valves They provide a quality solution and For most water and cooled applications. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange OPTIONS Control Rods Oil & Gas Water and Waste Suction and discharge pump Seawater Chemical lines More information Copper resseters for installation 5/8A", 5/8A" x 3/4A", 3/4A", 1A", 1 1/2 A" 2A" Water meters 11/12 Table of Contents Page Page Page Content Resetters Content Resettlers Content Resettlers Content Resettlers 5/8A", 5/8A" x 3/4A", 3/4A", 1A" Horizontal Input & Output Series 710 More information Technical Services: Tel: (800) 381-9312 / Fax: (800) 791-5500 Series ELO-231B 11.2 K-Factor Vertical and horizontal side wall valves. More information type 3353 of the valve of the valve of the valve of the valve on / off with the nominal actuator of the actuator of the pneumatic piston DN 15 to 50 50 2 to 2) Nominal pressure PN Temperature range 10 to 180 C Balloon valve with angular seat More information Contact www.tyco-fire.com Model SW-20 and SW-24 11.2 Factor K Extended Ordinary Hazard Horizontal Sidewall (Standard) General Description 11.2 Factor K, Extended Ordinary s, Standard are More information SimplexGrinnell TXMAS Electronic Commerce Ferguson Fire and Fabrication Sprinkler Price List Based on SG GSA Fire & Security Products Contract GS-07F-0396M, Mod PO-0099 January 30, 2013 Product ID Description TXMAS More information IP6-compatible PUR jacket on cable Shielded system Shroud on RJ45 Screw Rewireable Flex connector PCB mounted terminal panel connector IDC Connector Earom lead version Learn More System Accessories Pricing Page 0 Cash 7/02 Firetrace Tubing 200 005 Firetrace Protection Tubing (FDT) (Per Foot) (Available in continuous lengths up to 333 feet.) Accessories 400 001 400 004 400 061 400 060 Read more FIRE FIGH MANUAL AND REMOTE CONTROLADO Simple wiring only 2 electric lines Common Maximum range ZOOM I RANGE I ACCESSORIES I AFTER RESEARCH SERVICE  MANUAL TRAINING & REMOTE Petrojet More information APPLICATIONS Process Industry Low Alkaline Alcaes Tablets Air Pulp & Paper MODELS ASM  Connection Flange

